

Package: sig (via r-universe)

September 7, 2024

Type Package

Title Print Function Signatures

Version 0.0-6

Date 2016-03-30

Author Richard Cotton [aut, cre]

Maintainer Richard Cotton <richierocks@gmail.com>

Description Print function signatures and find overly complicated code.

URL <https://bitbucket.org/richierocks/sig>

BugReports <https://bitbucket.org/richierocks/sig/issues>

Depends R (>= 2.15.0)

License Unlimited

LazyLoad yes

LazyData yes

Roxygen list(wrap = FALSE)

Acknowledgments Development of this package was partially funded by the Proteomics Core at Weill Cornell Medical College in Qatar <<http://qatar-weill.cornell.edu>>. The Core is supported by 'Biomedical Research Program' funds, a program funded by Qatar Foundation.

Collate 'sig.R' 'list_sigs.R' 'as.R' 'is.R' 'sig_report.R' 'indexing.R' 'utils.R' 'write_sigs.R'

Repository <https://richierocks.r-universe.dev>

RemoteUrl <https://bitbucket.org/richierocks/sig>

RemoteRef HEAD

RemoteSha 7ef618eaa1310ac34427e184c46f253863a4101e

Contents

as.list.sig	2
as.sig	3
as.siglist	4
backquote	5
exponential_cut	5
fix_fn_names	6
is.sig	7
is.siglist	7
list_sigs	8
pkg2env	9
print_engine	9
sig	10
sig_report	11
source_to_new_env	13
toString.sig	13
toString.siglist	14
write_sigs	15
[16
Index	18

as.list.sig	<i>Convert to list</i>
-------------	------------------------

Description

Strips class attributes to return a list.

Usage

```
## S3 method for class 'sig'
as.list(x, ...)

## S3 method for class 'siglist'
as.list(x, ...)

## S3 method for class 'sigreport'
as.list(x, ...)
```

Arguments

x	sig, siglist or sigreport object.
...	Passed from other as.list methods.

Value

A list.

Examples

```
as.list(sig(read.csv))
head(as.list(list_sigs(pkg2env(stats))))
as.list(sig_report(baseenv()))
```

as.sig	<i>Coerce object to be a sig</i>
--------	----------------------------------

Description

Coerces an object to be a sig.

Usage

```
as.sig(x, ...)
```

Default S3 method:
as.sig(x, ...)

S3 method for class 'siglist'
as.sig(x, ...)

S3 method for class 'list'
as.sig(x, ...)

S3 method for class 'sig'
as.sig(x, ...)

Arguments

x	Object to coerce.
...	Passed to other as.sig methods.

Value

An object of class sig.

See Also

[as.siglist](#)

Examples

```
as.sig(
  list(name = "fun", alist(x =, y = 1))
)
```

as.siglist *Coerce object to be a siglist*

Description

Coerces an object to be a siglist.

Usage

```
as.siglist(x, ...)  
  
## S3 method for class 'sig'  
as.siglist(x, ...)  
  
## S3 method for class 'list'  
as.siglist(x, ...)  
  
## S3 method for class 'siglist'  
as.siglist(x, ...)
```

Arguments

x	Object to coerce.
...	Passed to other as.siglist methods.

Value

An object of class siglist.

See Also

[as.sig](#)

Examples

```
as.siglist(list(  
  sig(mean),  
  list(name = "fun", alist(x =, y = 1))  
))
```

backquote	<i>Wrap in backquotes</i>
-----------	---------------------------

Description

Wraps strings in backquotes.

Usage

```
backquote(x)
```

Arguments

x A character vector.

Value

A character vector.

Note

Existing backquote characters are escaped with a backslash.

See Also

[sQuote](#)

Examples

```
## Not run:  
backquote(c("foo bar", "a`b`c"))  
  
## End(Not run)
```

exponential_cut	<i>Cut with exponential breaks</i>
-----------------	------------------------------------

Description

Wrapper to cut for positive integers.

Usage

```
exponential_cut(x)
```

Arguments

x A vector of positive integers.

Value

A factor.

Note

The breaks are 1, 2, 3 to 4, 5 to 8, etc. No input checking is done; use at your peril.

See Also

[cut](#)

Examples

```
## Not run:  
exponential_cut(c(1:10, 500))  
  
## End(Not run)
```

fix_fn_names	<i>Fix names for sigs</i>
--------------	---------------------------

Description

Make anonymous functions and special functions safe.

Usage

```
fix_fn_names(fn_name)
```

Arguments

fn_name A character vector.

Value

A character vector.

Note

Strings beginning with “function” are given the value “. . anonymous . .”.
Special function names are wrapped in backquotes.

Examples

```
## Not run:
fix_fn_names(c("%foo%", "?", "foo bar", "repeat", "function"))

## End(Not run)
```

is.sig	<i>Is the input a sig?</i>
--------	----------------------------

Description

Does the input inherit from “sig”?

Usage

```
is.sig(x)
```

Arguments

x Object to test.

Value

TRUE if the object inherits from class “sig”, and FALSE otherwise.

Examples

```
stopifnot(
  is.sig(sig(with)),
  !is.sig(with)     #functions are not their signatures.
)
```

is.siglist	<i>Is the input a siglist?</i>
------------	--------------------------------

Description

Does the input inherit from “siglist”?

Usage

```
is.siglist(x)
```

Arguments

x Object to test.

Value

TRUE if the object inherits from class “siglist” and `is.sig` returns TRUE for each element of the input, and FALSE otherwise.

Examples

```
stopifnot(
  !is.siglist(sig(with))    #1 sig is not a siglist.
)
```

list_sigs	<i>List the signatures of all functions</i>
-----------	---

Description

Lists the signatures of all functions in an environment or file.

Usage

```
list_sigs(x, pattern = NULL, ...)

## Default S3 method:
list_sigs(x, ...)

## S3 method for class 'environment'
list_sigs(x, pattern = NULL, ...)

## S3 method for class 'character'
list_sigs(x, ...)
```

Arguments

x	An environment or the the path to a file.
pattern	An optional regular expression. Only names matching pattern are returned.
...	Currently ignored

Value

An object of class siglist, which is a list of sig obejcts.

Examples

```
#From a package
list_sigs(pkg2env(graphics))
#Just functions beginning with 'a'.
list_sigs(pkg2env(graphics), pattern = "^a")
#From a file
list_sigs(system.file("extdata", "sample.R", package = "sig"))
```

pkg2env	<i>Get environment of a package.</i>
---------	--------------------------------------

Description

Utility function to get the environment of a package on the search path.

Usage

```
pkg2env(pkg)
```

```
pkg2env_(pkg)
```

Arguments

pkg A package.

Value

the environment corresponding to pkg.

See Also

[list2env](#)

Examples

```
# Non-standard evaluation version
pkg2env(graphics)

# Standard evaluations versions
pkg2env_("tools")
pkg2env_(~ utils)
pkg2env_(quote(stats))
```

print_engine	<i>Workhorse of the print methods</i>
--------------	---------------------------------------

Description

Wraps toString methods with cat.

Usage

```
print_engine(x, ...)
```

Arguments

x	Object to print
...	Passed to toString.

Value

The input is invisibly returned, but the function is mostly invoked for the side effect of printing the object.

Note

Not intended for general consumption. This function is only exported because of package build requirements.

sig	<i>Generate a function signature object</i>
-----	---

Description

Generates a signature object for a function.

Usage

```
sig(fn, name_override)
```

Arguments

fn	A function.
name_override	Override the default function name. See examples.

Value

A list, with the elements

- name The name of the function.
- args The arguments of the function.

Note

Anonymous functions are given the name `"..anonymous.."`.

Nonstandard names (`"foo bar"`), assignment fns (`"foo<-"`), operators (`"` in backquotes).

Examples

```

sig(R.Version)           #no args
sig(scan)                 #lots of args
sig(function(x, y) {x + y}) #anonymous
sig(sum)                  #primitive
fn_list <- list(
  mean = mean,
  var = var
)
lapply(fn_list, sig)      #names are a mess
Map(                       #use Map for lists
  sig,
  fn_list,
  names(fn_list)          #Map mangles names, so override
)

```

sig_report

Summarise function complexity of a file or environment

Description

Summarise function complexity of a file or environment

Usage

```

sig_report(x, ...)

## Default S3 method:
sig_report(x, ...)

## S3 method for class 'environment'
sig_report(x, too_many_args = 10, too_many_lines = 50,
  length_metric = c("deparse", "body"), ...)

## S3 method for class 'character'
sig_report(x, ...)

## S3 method for class 'sigreport'
print(x, ...)

```

Arguments

x	A path to an R file or an environment.
...	Passed to sig_report.environment.
too_many_args	Upper bound for a sensible number of args.
too_many_lines	Upper bound for a sensible number of lines.
length_metric	Either "deparse" or "body". See note.

Details

sig_report summarises the number of input arguments and the number of lines of each function in an environment of file, and identifies problem files, in order to help you refactor your code. If the input is a path to an R file, then that file is sourced into a new environment and the report is generated from that. The number of lines of code that a function takes up is subjective in R; this function gives you a choice of length(deparse(fn)) or length(body(fn)), depending upon the value of length_metric. The body metric tends to give smaller values than deparse, so you may want to reduce the too_many_lines argument.

Value

An object of class “sigreport” with the elements:

- n_vars Number of variables.
- n_fns Number of functions.
- n_args Table of the number of args of each function.
- too_many_args Upper bound for a sensible number of args.
- fns_with_many_args Names of each function with more args than too_many_args.
- n_lines Table of the number of lines of each function body.
- too_many_lines Upper bound for a sensible number of lines.
- long_fns Names of each function with more lines than too_many_lines.

Examples

```
# Summarise function complexity in an environment
sig_report(pkg2env(stats))
# Summarise function complexity in a file

# From a file
tmp <- tempfile(fileext = ".R")
writeLines(c(toString(sig(scan)), deparse(body(scan))), tmp)
sig_report(tmp)

# From an environment, adjusting the cutoff for reporting
sig_report(
  baseenv(),
  too_many_args = 20,
  too_many_lines = 100
)
# Alternate length metric
sig_report(baseenv(), length_metric = "body")
```

source_to_new_env	<i>Source a file into a new environment.</i>
-------------------	--

Description

Silently sources a file into a new environment, returning that environment.

Usage

```
source_to_new_env(file, encoding = getOption("encoding"))
```

Arguments

file	a file to source.
encoding	character encoding of that file.

Value

An environment containing the sourced variables.

toString.sig	<i>Print a sig object</i>
--------------	---------------------------

Description

Prints a function signature object.

Usage

```
## S3 method for class 'sig'
toString(x, width = getOption("width"),
  exdent = nchar(x$name), ...)

## S3 method for class 'sig'
print(x, width = getOption("width"), exdent = nchar(x$name),
  ...)
```

Arguments

x	An object of class sig.
width	Width of string to display.
exdent	Non-negative integer specifying the indentation of subsequent lines in the string.
...	Passed to toString

Value

toString creates a string representation of a function signature. print is mostly invoked for the side effect of printing a function signature, invisibly returning its input.

Examples

```
print_default_sig <- sig(print.default)
print(print_default_sig)
print(print_default_sig, width = 40)
print(print_default_sig, width = 40, exdent = 2)
toString(print_default_sig)
```

toString.siglist	<i>Print a siglist object</i>
------------------	-------------------------------

Description

Prints a list of function signature objects.

Usage

```
## S3 method for class 'siglist'
toString(x, width = getOption("width"), ...)

## S3 method for class 'siglist'
print(x, width = getOption("width"), ...)
```

Arguments

x	An object of class siglist.
width	Width of string to display.
...	Passed to the equivalent sig method.

Value

toString creates a string representation of a function signature. print is mostly invoked for the side effect of printing a function signature, invisibly returning its input.

Examples

```
method_sigs <- list_sigs(pkg2env(methods))
print(method_sigs)
print(method_sigs, width = 40)
print(method_sigs, width = 40, exdent = 2)
toString(method_sigs)
```

write_sigs	<i>Write sigs to file</i>
------------	---------------------------

Description

Writes a list of function signatures to a file.

Usage

```
write_sigs(x, file = stdout(), ...)  
  
## Default S3 method:  
write_sigs(x, file = stdout(), ...)  
  
## S3 method for class 'siglist'  
write_sigs(x, file = stdout(), ...)  
  
## S3 method for class 'environment'  
write_sigs(x, file = stdout(), ...)  
  
## S3 method for class 'character'  
write_sigs(x, file = stdout(), ...)
```

Arguments

x	A list of function signatures. See details.
file	A file path or connection to write the output to (stdout by default).
...	passed to toString.siglist.

Details

Where x is an object of class lcodesiglist, the function essentially calls writeLines(tostring(x)). If the input is a single function signature (of class sig), then it is coerced into a siglist. If the input is an environment or path to a file, then list_sigs is called on the input before writing.

Value

A character vector of the lines that were written to file is invisibly returned. Mostly invoked for the side effect of writing function signatures to a file.

Examples

```
#Step by step:  
#First, list some sigs.  
utils_sigs <- list_sigs(pkg2env(utils))  
#Without a file argument, sigs are just printed to the console.  
head(write_sigs(utils_sigs))
```

```

#Write to a file
tmpf <- tempfile("sig", fileext = ".R")
write_sigs(utls_sigs, tmpf)
## Not run:
Open the file we've just written
shell(tmpf, wait = FALSE)

## End(Not run)
#Can also list and write in one line.
tmpf2 <- tempfile("sig", fileext = ".R")
write_sigs(pkg2env(grDevices), tmpf2)
#Single sigs are coerced to siglists
write_sigs(sig(stats::var))

```

[*Indexing for siglists*]

Description

Get or set a subset of a siglist.

Usage

```

## S3 method for class 'siglist'
x[i, ...]

## S3 method for class 'siglist'
x[[i, ...]]

## S3 replacement method for class 'siglist'
x[...] <- value

## S3 replacement method for class 'siglist'
x[[...]] <- value

```

Arguments

x	A siglist object.
i	An integer vector index.
...	Passed from other index methods.
value	A value to set the subset to.

Value

A siglist.

See Also

[Extract](#)

Examples

```
methods_sigs <- list_sigs(pkg2env(methods))
methods_sigs[1:5]
methods_sigs[[1]]
```

Index

[, 16
[<-.siglist ([), 16
[[.siglist ([), 16
[[<-.siglist ([), 16

as.list.sig, 2
as.list.siglist (as.list.sig), 2
as.list.sigreport (as.list.sig), 2
as.sig, 3, 4
as.siglist, 3, 4

backquote, 5

cut, 6

exponential_cut, 5
Extract, 16
Extract.siglist ([), 16

fix_fn_names, 6

is.sig, 7
is.siglist, 7

list2env, 9
list_sigs, 8

pkg2env, 9
pkg2env_ (pkg2env), 9
print.sig (toString.sig), 13
print.siglist (toString.siglist), 14
print.sigreport (sig_report), 11
print_engine, 9

sig, 10
sig_report, 11
source_to_new_env, 13
sQuote, 5

toString.sig, 13
toString.siglist, 14

write_sigs, 15